


# output module CPX-8DA

Part number: 541482

FESTO

With channel oriented diagnosis.



## Data sheet

Feature	Value
Dimensions W x L x H	(incl. interlinking block and connection technology) 50 mm x 107 mm x 50 mm
No. of outputs	8
Diagnosis	Short circuit/overload per channel Undervoltage, outputs
Parameters configuring	Fail-safe mode per channel Forcing per channel Idle mode per channel Behaviour after short circuit Module monitoring
LED displays	1 group diagnostics 8 channel diagnostics 8 channel status
Protection (short circuit)	Internal electronic fuse protection per channel
Operating voltage range DC	18 ... 30 V
Intrinsic current consumption at operating voltage	Typically 16 mA
Max. power supply per channel	0.5 A (12 W lamp load)
Max. residual current outputs per module	4 A
Nominal operating voltage DC	24 V
Electrical isolation channel – internal bus	Yes, for intermediate supply
Electrical isolation channel – channel	No
Corrosion resistance classification CRC	1 - Low corrosion stress (when installed)
Storage temperature	-20 ... 70 °C
Protection class	Depending on the connection block
Ambient temperature	-5 ... 50 °C
Product weight	49 g
Characteristic curve, outputs	IEC1131-T2
Switching logic, outputs	PNP (positive-switching)
Material housing	PA-reinforced PC